

Xerox 3030 Engineering Copier

The Xerox 3030 Engineering Copier is a point-of-need plain-paper copier with powerful productivity features. It's compact and environmentally friendly. The 3030 gives you walk-up convenience, automatic operation and a clear, easy-to-use graphic interface. Taking full advantage of the 3030's functionality is as simple as pushing a few buttons.

Document Input / Types

- Maximum size 36" x 20' long in single copy mode; 36" x 60" long multicopy mode
- Minimum size 8 1/2" x 11" (portrait)
- Opaque, translucent and transparent documents. Note: A document carrier (8R3628) is recommended for damaged or very delicate documents

Productivity

- Warm-up time Standby less than 3 minutes; cold start 5-7 minutes
- First Copy Out Time
- (FCOT) Less than 20 seconds D size (24" x 36")
- Multiple copies Selectable, 1-15 copies per document
- Copy throughxeroxut 2 E size (36" x 48") per minute; 4 D size (24" x 36") per minute; 6 C size (18" x 24") per minute

Media

- Type 20 lb. xerographic bond, 20 lb. xerographic Zero Solvent vellum and .004 drafting film
- Media Supply Roll stock selectable from one on-line feed roll; either 36" x 500' bond or vellum or 36" x 150' .004 drafting film. (Manual bypass for special media applications)

Physical Characteristics

- Product size Height 46.25"; Width 57"; Depth 27"; Weight: 500 lbs
- Installation Space 105" x 87"
- Agency approvals UL and CSA

Power Requirements

- 115 VAC/20 amp dedicated line